




ZX80W FULLY RUGGED TABLET

- Processeur octa-core Qualcomm® QCS6490 avec Windows 11 IoT Enterprise LTSC
- Conception légère avec batteries haute capacité remplaçables à chaud pour un fonctionnement prolongé et ininterrompu sur le terrain
- Écran LumiBond FHD de 8 pouces avec technologie Getac de lecture en plein soleil (1 000 nits) et écran tactile capacitif
- Certification MIL-STD-810H et IP67, avec résistance aux chutes de 1,8 m (6 pi)
- Plusieurs configurations avec des outils de gestion de niveau entreprise dans un facteur de forme fin et léger



SPECIFICATIONS

Generation
G1

Operating System
Windows 11 IoT Enterprise LTSC

Mobile Computing Platform
Qualcomm® QCS6490, Octa-core 1.9GHz
Max. 2.7GHz

Graphics
Qualcomm® Adreno™ 643 GPU

NPU
Qualcomm® Hexagon™ Processor,
up to 13 TOPS with 6th Qualcomm AI Engine

Display
8" Wide Viewing Angle TFT LCD WUXGA (1920 x 1200)
Protection film
1,000 nits LumiBond display with Getac sunlight readable technology
Capacitive multi-touch screen

Storage & Memory
12GB LPDDR5, 256GB UFS

Keyboard
Power button
3 tablet programmable buttons
Default: Windows Key, Volume up, Volume down

Pointing Device
Touchscreen
- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

Audio
Integrated speakers
Integrated dual-array microphone

Expansion Slot
Optional: 1D/2D imager barcode reader

I/O Interface
8MP webcam x 1
16MP auto focus rear camera x 1
Audio in/out combo x 1
USB 3.2 Gen 1 Type-C (with DisplayPort & Power Delivery) x 1
MicroSD x 1 or Optional: Hybrid SIM card (Nano-SIM, 4FF)
tray with MicroSD x 1ⁱ
Docking connector x 1
Optional: SIM card slot x 1 (Nano-SIM, 4FF)^{ix}
Optional: RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface
Wi-Fi 6E 802.11ax
Bluetooth (v5.2)ⁱⁱ
Dedicated L1/L5 GPSⁱⁱⁱ
Optional: 4G LTE mobile broadbandⁱ
Optional: 5G Sub-6^j
Optional: Dual SIM (Nano-SIM 4FF and e-SIM)^{i, ix}

Security Feature
fTPM (Qualcomm TrustZone)
Getac Secure Erase

Power
Internal battery (3.86V, typical 4060mAh; min. 3950mAh)
LifeSupport battery swappable technology

Swappable Battery Options:
Battery bay cover (Default)
Battery (3.84V, typical 4990mAh; min. 4870mAh)
High capacity Li-ion battery (3.84V, typical 9980mAh; min. 9470mAh)

Dimension (W x D x H) & Weight
234 x 149.8 x 17.6mm (9.21" x 5.89" x 0.69")
590g (1.3lbs)^{iv}

Rugged Feature
MIL-STD-810H certified
IP67 certified
Vibration & 6ft (1.8m) drop resistant^v
Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D)^{vi}

Environmental Specification
Temperature^{vii}:
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Pre-installed Software
Getac Utility
Getac KeyWedge Barcode Reader Utility (trail version)

Optional software
Getac KeyWedge Barcode Reader Utility
Getac Monitoring

Accessories
Optional:
Carry bag
Battery (3.84V, typical 4990mAh; min. 4870mAh)
High capacity Li-ion battery (3.84V, typical 9980mAh; min. 9470mAh)
DC-DC vehicle adapter (65W, 12-32VDC)
Multi-Bay charger (Dual-Bay)
Multi-Bay charger (Eight-Bay)
Digitizer pen with tether
Capacitive stylus with tether
Protection film
Hand strap with stylus holder
Rotating hand strap with kickstand
Shoulder strap (2-point)
Vehicle cradle^{viii}
Vehicle dock^{viii}
Office dock
65W USB-C AC Adapter

Bumper-to-Bumper warranty
Les accidents surviennent quand on s’y attend le moins, en particulier lorsque les produits sont soumis à des conditions difficiles, et peuvent engendrer une mise hors service des équipements et des périodes d’interruption très coûteuses. C’est pourquoi Getac propose de prendre en charge les dommages accidentels dans sa garantie Bumper-to-Bumper, afin de réduire les coûts informatiques de votre entreprise. La garantie Bumper-to-Bumper, c’est la tranquillité d’esprit assurée. En quelques jours seulement, vous êtes certain de récupérer vos appareils opérationnels.

Standard
3 ans Bumper-to-Bumper

ZX80W FULLY RUGGED TABLET

- I. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers.
- II. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- III. Support GPS, GLONASS, Galileo and BeiDou.
- IV. Weight and dimensions vary from configurations and optional accessories.
- V. Drop test results vary from configurations and optional accessories.
- VI. Available with limited configurations and environment conditions.
- VII. Tested by an independent third-party test lab following MIL-STD-810H.
- VIII. Gamber-Johnson vehicle dock and cradle are e-mark certified.
- IX. Units with 4G/5G option come with an embedded SIM card slot.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



GETAC TECHNOLOGY CORPORATION

12, avenue du Québec Bâtiment Goyave 91140
Villebon sur Yvette Tel: +33 160 12 80 60
Sales-Getac-France@getac.com |
www.getac.com/fr/

Copyright © 2026 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Les informations sont fournies ici pour référence seulement, les spécifications disponibles doivent faire l'objet d'un devis sur demande.